



GLAZE PLUS

# TECHNICAL DATA SHEET

## DURA SEAL +

## DURA SEAL +



### DESCRIPTION

**DURA SEAL+** is a premium solvent-based deep penetrating impregnating sealer specially formulated to protect porous natural stone and tile surfaces from water penetration and common staining. The advanced formulation penetrates deep into the substrate, forming an invisible protective barrier within the pores while maintaining the natural breathability of the surface. The product provides long-lasting protection against moisture ingress and everyday staining while offering slight natural colour enhancement without excessive darkening. Suitable for both interior and exterior applications.

### PRODUCT TYPE

Deep Penetrating Solvent-Based Impregnating Sealer (Non-Film Forming)

### ADVANTAGES

- Deep penetrating protection
- Water repellent performance
- Stain resistant protection
- Breathable surface protection
- Interior & exterior use
- Long lasting durability
- Slight natural colour enhancement
- Invisible protection within the substrate

## AREAS OF APPLICATION

- Marble flooring and wall surfaces
- Granite surfaces
- Limestone installations
- Slate stone applications
- Terrazzo flooring
- Terracotta and clay tiles
- Brick surfaces
- Natural stone cladding
- Interior and exterior stone installations

## KEY PROPERTIES

- Deep penetrating formula
- Water repellent protection
- Stain resistant performance
- Breathable protection
- Allows moisture vapour transmission
- Slight natural colour enhancement
- Non-film forming protection
- Long lasting protection

## METHOD OF APPLICATION

Application can be carried out using a brush, lint-free cloth, roller or low-pressure spray equipment. Apply evenly until the surface is saturated. Allow the product to penetrate the substrate and remove any excess material remaining on the surface. Additional coats may be applied depending on substrate porosity.

## TECHNICAL DATA

Property	Value
Product Type	Solvent-Based Impregnating Sealer
Appearance	Clear Liquid
Colour	Transparent
Finish	Natural Enhanced Finish
Density	Approx. 0.80–0.90 g/cm <sup>3</sup>
Coverage	Approx. 5–15 m <sup>2</sup> /L/Coat
Application Method	Brush, Roller, Cloth, Spray
Recoat Time	Approx. 2 Hours
Light Foot Traffic	After 24 Hours
Full Cure	24–48 Hours
Water Repellency	Excellent
Stain Resistance	Excellent
Breathability	Maintained
Interior Use	Yes
Exterior Use	Yes

## CLEANING OF TOOLS

Clean tools immediately after use with a suitable solvent cleaner before the material dries.

## INSTRUCTIONS FOR USE

1. Test **DURA SEAL+** on a small inconspicuous area before full application.
2. Ensure the surface is clean, dry and free from dust, grease, wax and contaminants.
3. Remove any cement residues, efflorescence or deposits before treatment.
4. Thoroughly rinse and allow the surface to dry completely.
5. Apply **DURA SEAL+** evenly using a brush, lint-free cloth, roller or low-pressure spray.
6. Allow the product to penetrate for approximately 5 minutes.
7. Remove excess material remaining on the surface.
8. Apply additional coats if required depending upon substrate porosity.
9. Allow approximately 2 hours between coats.
10. Light foot traffic is recommended only after approximately 24 hours.

## STORAGE

Store in original unopened packaging in a cool, dry location between 5°C and 30°C. Protect from direct sunlight and excessive heat.

## HEALTH & SAFETY

- Keep out of reach of children.
- Wear suitable gloves and eye protection.
- Avoid prolonged skin contact.
- Ensure adequate ventilation during application.
- Refer to Safety Data Sheet for complete safety information.

## TECHNICAL SUPPORT

**Admin Office** C401 Swami narayan Business Park Narol Circle Ahemdabad - 382405

Website : [www.glazeplus.in](http://www.glazeplus.in) | Email : [sales@glazeplus.in](mailto:sales@glazeplus.in) | Helpline no. +918368077496