



GLAZE PLUS

TECHNICAL DATA SHEET

DURA SEAL (– Natural Look Stone Impregnator)

Dura seal (– Natural Look Stone Impregnator)



DESCRIPTION

DURA SEAL Natural Look Stone Impregnator is a ready-to-use, deep-penetrating protective treatment based on modified siloxane technology. The product penetrates the stone substrate through capillary action and forms an invisible, breathable barrier that significantly reduces water and dirt absorption while preserving the stone's natural appearance. The colour of the stone is normally not enhanced. On certain dense or dark stones, a slight colour intensification may occur due to the natural characteristics of the material. This is not a product defect.

PRODUCT TYPE

Penetrating stone impregnator (non-film forming)

ADVANTAGES

- Preserves natural stone appearance
- Invisible, non-film forming protection
- No gloss or wet look
- Breathable – vapour permeable
- Water & dirt repellent
- UV resistant & weather stable
- Suitable for interior & exterior use
- Long-lasting protection

Areas of Application

- Suitable for absorbent mineral surfaces such as:
- Natural stone (marble, granite, limestone, sandstone)
- Concrete and concrete ashlar
- Bricks and sand-lime bricks
- Mineral-based plaster

Key Properties

- Preserves natural appearance of stone
- Invisible, non-film forming impregnation
- Water & dirt repellent
- Vapour permeable (breathable)
- UV resistantLong-lasting protective effect

Method of Application

Application can be carried out using a brush, mop, or low-pressure airless spray equipment. Apply the product evenly until the surface is saturated. Avoid puddle formation.

TECHNICAL DATA

Property	Value
Chemical base	Modified siloxane
Appearance	Colourless to yellowish
Density	approx. 0.76 g/cm ³
Application form	Ready to use
Coverage	approx. 5–20 m ² /L (depending on absorbency)
Application temperature	+15°C to +25°C
Touch dry	approx. 40–50 minutes
Full protective effect	after 2–3 hours
Colour change	Normally not enhanced
UV resistance	Excellent
Vapour permeability	Maintained

Cleaning of Tools

- Clean tools immediately after use with suitable solvent or cleaning agent before material dries

Instructions for Use

1. Ensure the surface is clean, completely dry, and free from dust, grease, wax, or other residues.
2. Apply DURA SEAL evenly using a brush, mop, or low-pressure spray until the surface is fully saturated.
3. Allow the product to penetrate the surface.
4. After approx. 20 minutes, remove any excess material that has not been absorbed using a clean, dry cloth.
5. Do not allow surplus material to dry on the surface.
6. If required, a second application may be applied wet-in-wet.
7. The water-repellent effect develops after a few minutes; full protection is achieved after 2–3 hours.

Storage

Store in a cool, dry, frost-free place in the original, tightly closed container. Shelf life: 24 months from date of manufacture when stored correctly.

Health & Safety

- For professional use
- Use appropriate personal protective equipment..
- Avoid contact with skin and eyes.
- If contact occurs wash immediately with plenty of water. Remove contact lenses if possible.
- Keep out of reach of children.
- Always dispose of empty packaging responsibly.
- Keep children and pets away from treated areas until fully cured.

TECHNICAL SUPPORT

C401 - Swami Narayan Business Park, Narol Circle Ahmedabad - 382405
| www.glazeplusitaly.com | www.glazeplus.in | sales@glazeplus.in