



GLAZE PLUS

# TECHNICAL DATA SHEET

## GLAZE PROFILL-900

## GLAZE PROFILL-900



### DESCRIPTION

GLAZE PROFILL-900 is polymer modified cement based non sanded grout which is ideal for fitting & finishing of all types of tiles, marble and stone's joints in interior or exterior for both floors & walls, grouting of joint treatment with resistant water type joint.

### USES

- Vitrified tile
- Marble
- Natural stone
- To fill the tile joints with grout so as to create strong long lasting tile joints

### ADVANTAGES

- Extra fine finish
- High resistant to sunlight
- Easy to clean

- High performance grout
- Excellent water resistance
- Designed for grouting wall & floor tiles, marbles, & stones etc.
- Natural antibacterial

## COMPLIANCE STANDARD

EN 12004:2019

## METHOD OF APPLICATION

- Clean tile joint from all dusts, oils etc. and the joint should be dry.
- Mix 320 ml of clean water to 1 Kg of GLAZE PROFILL-900. If we are adding POLY GROUT then water content may reduce to 80 to 100 ml.
- Apply GLAZE PROFILL-900 firmly to ensure that the tile spaces are completely filled.
- Remove surplus grout and Allow grout to firm up then smooth the joints by wiping with slightly damp cloth or sponge.

## TECHNICAL INFORMATION

Properties	Results
Pot life @ 20°C	4 hours
Pot life @ 20°C	3 hours
Mixed Density	1.90kg/liter (brush able Consistency)
Tensile strength	2 N/ mm <sup>2</sup> (at 1.5mm Thickness)
Colors	Shed card available
Application temperature	Not less than 10°C
Toxicity	Non-toxic
Adhesion to Concrete	>1N/mm <sup>2</sup>

GLAZE PROFILL-900 has a shelf life of 12 months if kept in a cool and dry place in unopened bags under room temperature (i.e. 27°C)

## PACKAGING

- 1Kg

## TECHNICAL SUPPORT

9/47 Subhash Nagar, New Delhi 110027 | C401 - Swami Narayan Business Park, Narol Circle Ahmedabad - 382405 | [www.glazeplusitaly.com](http://www.glazeplusitaly.com), [www.glazeplus.in](http://www.glazeplus.in) | [sales@glazeplus.in](mailto:sales@glazeplus.in)  
Helpline no. +91836807749