



GLAZE PLUS

TECHNICAL DATA SHEET

GRIPLOCK

GRIPLOCK



DESCRIPTION

GRIP LOCK is a high-performance water-based bonding agent designed to improve adhesion between smooth or low-absorption surfaces and plaster or mortar layers. The product penetrates deeply into the substrate and forms a strong bonding bridge, eliminating the need for hacking or mechanical roughening.

The formulation uses coarse and liquid particle bonding technology to ensure excellent grip and long-lasting adhesion.

Suitable for applications involving marble, granite, natural stone, concrete, and plaster surfaces.

Key Features:

- Single coat application
- Coarse & liquid particle bonding technology
- Excellent adhesion strength
- Fast initial drying
- Deep surface penetration
- Water-based and easy to apply
- Suitable for marble, granite & natural stone
- Large surface coverage

Application Area

- Recommended for improving bonding between:
 - Concrete surfaces
 - Cement-sand plaster
 - Gypsum plaster
 - Marble and granite stone backs
 - Natural stone surfaces

Technical Data

| Property | Value |
|---------------------|---------------------------|
| Product Type | Water-Based Bonding Agent |
| Appearance | Liquid |
| Colour | Milky / Light |
| Application | Brush or Roller |
| Coat Type | Single Coat |
| Initial Drying Time | approx. 10 minutes |
| Full Drying Time | approx. 24 hours |

Application Method

- Ensure the surface is clean, dry, and free from dust, oil, grease, or loose particles.
- Stir the product thoroughly before use.
- Apply a uniform single coat using a brush or roller.
- Allow the surface to dry before applying plaster or mortar.

Coverage

- Large surface coverage depending on substrate absorption.

Packaging • 1

Storage

- Store in a cool and dry place, away from direct sunlight.
- Keep container tightly closed after use.

Shelf Life

24 months from the manufacturing date when stored in unopened original packaging.

Safety Information

Avoid contact with eyes and skin
Use protective gloves during application
Keep out of reach of children
Refer to Safety Data Sheet for detailed safety instructions

TECHNICAL SUPPORT

Admin Office C401 Swami narayan Business Park Narol Circle Ahemdabad - 382405

Website : www.glazeplus.in | Email : sales@glazeplus.in | Helpline no. +918368077496