



GLAZE PLUS

TECHNICAL DATA SHEET

SUPER CRYSTAL SOLID WAX

SUPER CRYSTAL SOLID WAX**DESCRIPTION**

SUPER CRYSTAL SOLID WAX is a fast-drying, solvent-based solid wax to polish and restore surfaces without foot traffic, such as walls, tops and work surfaces.

Its formula, containing top-quality paraffin, gives an excellent shine to the surfaces on which it is used and at the same time, it enhances the tone and look.

SUPER CRYSTAL SOLID WAX also stands out for its quick, easy application, thanks to its fast-drying action. A surface treated with SUPER CRYSTAL SOLID WAX is also protected against water and stain penetration, thanks to its water- and oil-repellence, which also make successive cleaning and maintenance operations easier.

SUPER CRYSTAL SOLID WAX is generally used on natural stone surfaces but it can also be used on cotto, terracotta, cement agglomerates, cementine and terrazzo tiles.

CHARACTERISTICS AND BENEFITS

- Brings out the shine on the treated material
- Contains top-quality paraffin
- Quick and easy application
- Increases surface shine
- Leaves the surface with excellent water repellence
- Makes surface maintenance easier

- Will not yellow over time
- Fast drying
- Effective stain protection

USES

Product suitable for indoor and outdoor use.

Suitable for use on: Marble-cement agglomerate, Slate, Basaltina - Lava stone, Cementina, Clinker, Cotto, Granite, Limestone, Marble, Quartzite, Terracotta, Travertine

COVERAGE

20/25 m² /l

APPLICATION EQUIPMENT

Product application: Cloth, Spatula, Brush

Product polishing: Orbital or flexible polisher, arm polishing machine

APPLICATION STEPS

Preparing and cleaning the surface

1. Carefully clean the surface, making sure to remove any dust or dirt present.
2. Never apply SUPER CRYSTAL SOLID WAX to wet or damp surfaces.
3. To boost product penetration, we recommend warming the surface being treated.
4. Any adjacent surfaces not being treated with the product must be protected.

Application

5. Apply an even coat of product to a clean, dry surface with a spatula or a dry cloth, taking care to create the most even layer to cover the whole surface.
6. 5-10 minutes later but in any case on the completely dry layer of the product, proceed to polish the surface. This operation can be carried out manually on small surfaces, using a wool cotton cloth, white or wire wool pad. In case of larger areas, we recommend using a tool such as the orbital or flexible polisher or arm polishing machine, complete with white, felt or lambskin pad, or wire wool. Work the surface, brushing or polishing until all excess has been removed and the end result is both even and polished.

DRYING TIME

The product is fast drying and in any case, no more than 5-10 hours from application.

EQUIPMENT CLEANING

At the end of application, the equipment used can be cleaned using white spirit.

SAFETY

When applying the product, always use suitable personal protective equipment and carefully follow the instructions on the product safety data sheet.

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

24 months in the original, sealed packaging, stored in a cool, dry place.

INSTRUCTION AND GUIDELINES

- Never apply the product to wet or damp surfaces.
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

PHYSICAL TECHNICAL DATA

Aspect	Paste-like emulsion
Colour	Matt or transparent (depending on the storage temperature)
Odor	Solvent
Specific Gravity at 20°C	1520 ± 20 g/l

PACKAGING: 750 gms

TECHNICAL SUPPORT

9/47 Subhash Nagar, New Delhi 110027 | C401 - Swami Narayan Business Park, Narol Circle Ahmedabad - 382405 | www.glazeplusitaly.com, www.glazeplus.in | sales@glazeplus.in
Helpline no. +918368077496